


GD-1804S

Eco Solvent Printer (with four I3200-E1 heads)



Four I3200-E1 Heads



* 1.8m Four I3200-E1 Print Heads Speed

| | |
|---------------------|----------------------|
| 360x2400dpi - 4pass | 84 m ² /h |
| 720x1800dpi - 6pass | 62 m ² /h |
| 720x2400dpi - 8pass | 47 m ² /h |

Grando Eco Solvent Ink



Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subway advertising, shopping mall advertising signs etc.




● Technical Specifications

| | |
|-------------------------------|--|
| Model | GD-1804S |
| Print Head | Four I3200-E1 Print Heads |
| Printing Technology | Piezoelectric Inkjet |
| Acceptable Media | Width 71.6 in.(1820 mm) Thickness Maximum 59 mil(1.5 mm) Weight 132.2 lb.(60 kg) |
| Printing Width | 70.8 in.(1800 mm) |
| Ink Cartridges | Type Eco Solvent Ink Capacity 4*4 CISS (220ml ink cartridge with 1.5L ink tank) Color 4 colors (Cyan, Magenta, Yellow, Black) |
| Printing Resolution | Maximum 2400 dpi |
| Printing Speed | 4pass(360x2400dpi) : 84 sqm/h 6pass(720x1800dpi) : 62 sqm/h 8pass(720x2400dpi) : 47 sqm/h |
| Media Heating System | Integrated post heater & Infrared Dryer & Fan system |
| Interface | USB 2.0 |
| Power Supply | AC 220V ± 10%, 50/60 HZ |
| Dimensions(with stand) | 125.3(W)x38.1(D)x54.5(H) in. (3213(W)x970(D)x1388(H) mm) |
| Weight(with stand) | 882 lb. (400 kg) |
| Package Dimensions | Entirety Packing : 132.8(W)x39.8(D)x62.3(H) in. (3380(W)x1010(D)x1600(H) mm) Split Packing: 132.1(W)x31.4(D)x40.1(H) in. (3360(W)x800(D)x1020(H) mm) |
| Package Weight | Entirety Packing : 1102.5 lb. (500 kg) Split Packing : 860 lb. (390 kg) |
| Environment | Power on Temperature: 59 ℉ to 90 ℉ [15 ℃ to 32 ℃] (68 ℉ [20 ℃] / Humidity: 35 to 80% (no condensation) Power off Temperature: 41 ℉ to 104 ℉ [5 ℃ to 40 ℃] / Humidity: 20 to 80% (no condensation) |
| Accessories | USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc. |



THK high-precision mute rail



High-precision and high-stability tensioning pulley system



The automatic cleaning assembly adds a single-way valve to increase the stability of the ink supply



New pinch roller structure of three in group brings more stable feeding precision



Equipped with 4pcs authorized I3200-E1 print heads,high precision, high speed, high stability.



Bulky ink bottle with low-ink alarm represents the advanced vacuum concept of industrial application



Three stage heating system including pre-heater, print heater, and rear heater and platform vacuum system with adjustable power.



External power supply, intelligent rolling system.